

HSE 75 Series



HSE 75 Series

Single Cover • Duct Cover • Multipart Cover



Stainless steel
and aluminium,
hinged, floor
access covers for
cars and light
delivery vehicles

Image shown features aluminium cover

HSE 75 SERIES SPECIFICATIONS

FLOOR FINISHES: All types of hard floor finishes including ceramic tiles, marble, terrazzo, concrete, resin, wood or parquet.

PERFORMANCE: Cars and light delivery vehicles up to 5 tonne (5,000kg) pneumatic tyre wheel load.

FEATURES and BENEFITS: Can be fitted quickly and unobtrusively, ensuring minimum disruption. Unique cover sections are tapered for easy removal, frame sections give a good key to bedding mortar. Fitted with multi-link hinges and mild steel, powder coated gas springs. Double sealed with socket head securing bolts complete with all necessary removable sealing cross-members and support beams (where necessary). Recessed support beam pockets (where necessary). Lifting blocks are anchored to the inner frame. Stainless steel securing bolts are stiletto heel proof. Aluminium covers are available with a top edge seal to help prevent dirt, grout or grinding waste ingress.

FIRE RATING: To BS 476: Part 20: 1987 - 3 hours for Single cover, 2 hours for Duct and Multipart covers.

SIZES: See pages 6-7.

WEIGHT: Will require a maximum force of approx. 20kg to open when filled and installed correctly.

INSTALLATION: Go to www.howegreen.com